

ULTRA-FLOW™ 440**Blend of metal soaps of fatty acids**

Typical Properties

| | | |
|-------------------------|----|--|
| Appearance | | Beige pastilles ^[1] |
| Specific Gravity | | 1.1 |
| Dropping Point | °C | 95 |
| Zinc Content | % | 8.5 |
| Physiological behaviour | | Refer to Safety Data Sheet |
| Storage stability | | At least 2 years under normal conditions |

Packaging

25 kg polyethylene bag

Product Description

ULTRA-FLOW™ 440 is a processing additive for application in natural and synthetic rubber. Due to its unique composition it provides excellent improvement of processing properties for a broad range of elastomers of high and low polarity.

ULTRA-FLOW™ 440 improves filler dispersion, in particular silica and other mineral fillers.

ULTRA-FLOW™ 440 shows outstanding performance in extruded compounds, but also works well for transfer and injection moulding.

ULTRA-FLOW™ 440 complies with FDA 177.2600 and BfR XXI.

Dosage

1 to 3 phr

^[1] Our products are made from natural based raw materials and exhibit different shades. Depending on storage conditions and period the products may develop discoloration. These color variations do not deteriorate the product effectiveness.

The information and data contained in this data sheet are believed to be correct based on our best knowledge. Therefore, any information is given on condition that users shall make their own assessment of suitability of the product for a specific purpose. We accept no liability for any use or application unless explicitly stated by us. These data are not to be considered as specification.

All values stated in the properties are typical numbers only.