

## ULTRA-LUBE™ 200

### Blend of fatty acid derivatives and inorganic modifiers

---

#### Typical Properties

Appearance		White to beige pastilles <sup>[1]</sup>
Specific Gravity		1.1
Dropping Point	°C	56
Ash Content	%	21.5
Physiological behaviour		Refer to Safety Data Sheet
Storage stability		At least 2 years under normal conditions

#### Packaging

25 kg polyethylene bag

#### Product Description

**ULTRA-LUBE™ 200** is a processing additive for most rubber compounds. It shows outstanding performance as a dispersing aid for most fillers used in rubber compounding.

In injection and transfer moulding **ULTRA-LUBE™ 200** leads to faster mould filling due to its internal lubrication. An improved mould release can also be observed.

**ULTRA-LUBE™ 200** also works very well as an internal release agent that prevents sticking of compounds to mill rolls, calendaring bowls and internal mixer rotors.

**ULTRA-LUBE™ 200** does not adversely interfere with most curing systems. Due to its low dosage level there is little or no effect on physical properties of the finished goods.

#### Dosage

1 to 3 phr

<sup>[1]</sup> Our products are made from natural based raw materials and exhibit different shades. Depending on storage conditions and period the products may develop discoloration. These color variations do not deteriorate the product effectiveness.

The information and data contained in this data sheet are believed to be correct based on our best knowledge. Therefore, any information is given on condition that users shall make their own assessment of suitability of the product for a specific purpose. We accept no liability for any use or application unless explicitly stated by us. These data are not to be considered as specification.

**All values stated in the properties are typical numbers only.**