

Technical Data Sheet

ULTRA-LUBE[™] 330

Blend of high molecular weight esters and fatty acid soaps

Typical Properties

Appearance		Beige pastilles ^[1]
Specific Gravity		1.2
Dropping Point	°C	92
Ash Content	%	20.5
Physiological behaviour		Refer to Safety Data Sheet
Storage stability		At least 2 years under normal conditions

Packaging

25 kg polyethylene bag

Product Description

ULTRA-LUBE™ 330 is a general processing additive in most common polymers.

In highly filled compounds **ULTRA-LUBE™ 330** prevents the agglomeration of filler, which leads to better uniformity of physical properties of the finished goods. This is particularly beneficial for extrusion of rubber profiles.

The addition of **ULTRA-LUBE™ 330** leads to faster incorporation of filler.

ULTRA-LUBE™ 330 shows a positive influence on metal release, thus preventing sticking of the compounds to open mill rolls or internal mixer rotors. It also improves mould release after curing.

Dosage

1 to 3 phr

^[1]Our products are made from natural based raw materials and exhibit different shades. Depending on storage conditions and period the products may develop discoloration. These color variations do not deteriorate the product effectiveness.

The information and data contained in this data sheet are believed to be correct based on our best knowledge. Therefore, any information is given on condition that users shall make their own assessment of suitability of the product for a specific purpose. We accept no liability for any use or application unless explicitly stated by us. These data are not to be considered as specification. *All values stated in the properties are typical numbers only.*