

Technical Data Sheet

ULTRA-LUBE™ 420

Blend of fatty acid esters and soaps

Typical Properties

Appearance Off white to beige pastilles [1]

Specific Gravity 0.93 Dropping Point °C 90

Physiological behaviour Refer to Safety Data Sheet

Storage stability At least 2 years under normal conditions

Packaging

25 kg polyethylene bag

Product Description

ULTRA-LUBE™ 420 is a processing additive for applications in all elastomers.

ULTRA-LUBE™ 420 provides very good lubricating effects and helps to improve flow and mould release.

ULTRA-LUBE™ 420 shows excellent performance in highly filled EPDM compounds. No adverse effect on physicals is noted and its saturated structure makes it suitable for peroxide vulcanisation.

Dosage

EPDM 2 phr max.

NR/SBR 3 phr max.

Other 3 phr max.

The information and data contained in this data sheet are believed to be correct based on our best knowledge. Therefore, any information is given on condition that users shall make their own assessment of suitability of the product for a specific purpose. We accept no liability for any use or application unless explicitly stated by us. These data are not to be considered as specification.

All values stated in the properties are typical numbers only.

^[1] Our products are made from natural based raw materials and exhibit different shades. Depending on storage conditions and period the products may develop discoloration. These color variations do not deteriorate the product effectiveness.