

Technical Data Sheet

ULTRA-LUBE™ 480

Blend of metal soaps and fatty acid esters

Typical Properties

Appearance		Beige to yellow pastilles ^[1]
Specific Gravity		1.01
Dropping Point	°C	93
Physiological behaviour		Refer to Safety Data Sheet
Storage stability		At least 2 years under normal conditions

Packaging

25 kg polyethylene bag

Product Description

ULTRA-LUBE™ 480 is a highly effective processing additive for specialty polymers. Its unique structure is particularly suitable to improve flow and release of ECO compounds resulting in lower reject rate due to poor hot tear of ECO vulcanisates. Besides, it helps in preventing mould fouling.

ULTRA-LUBE™ 480 also works very well to improve extrusion characteristics of NBR/PVC blend compounds.

Dosage

0.5 to 2 phr

^{1]}Our products are made from natural based raw materials and exhibit different shades. Depending on storage conditions and period the products may develop discoloration. These color variations do not deteriorate the product effectiveness.

The information and data contained in this data sheet are believed to be correct based on our best knowledge. Therefore, any information is given on condition that users shall make their own assessment of suitability of the product for a specific purpose. We accept no liability for any use or application unless explicitly stated by us. These data are not to be considered as specification.

All values stated in the properties are typical numbers only.



Technical Data Sheet

The information and data contained in this data sheet are believed to be correct based on our best knowledge. Therefore, any information is given on condition that users shall make their own assessment of suitability of the product for a specific purpose. We accept no liability for any use or application unless explicitly stated by us. These data are not to be considered as specification.

All values stated in the properties are typical numbers only.