

## ULTRA-DFR™ 910

### Mixture of metal fatty acid soaps

---

#### Typical Properties

Appearance		Beige pastilles <sup>[1]</sup>
Specific Gravity		1.1
Dropping Point	°C	90
Physiological behaviour		Refer to Safety Data Sheet
Storage stability		At least 2 years under normal conditions

#### Packaging

25 kg polyethylene bag

#### Product Description

**ULTRA-DFR™ 910** effectively improves the flow and extrusion properties of EPDM compounds. Die swell is therefore greatly reduced.

The release effect of **ULTRA-DFR™ 910** is excellent during compounding and after curing. The surface finish of vulcanisates is highly improved.

The tendency of blooming is reduced to the minimum, due to the compatibility of **ULTRA-DFR™ 910** with EPDM.

**ULTRA-DFR™ 910** is applicable to both sulphur and peroxide cures. Low peroxide demand is expected too.

#### Dosage

1 to 3 phr

<sup>[1]</sup> Our products are made from natural based raw materials and exhibit different shades. Depending on storage conditions and period the products may develop discoloration. These color variations do not deteriorate the product effectiveness.

The information and data contained in this data sheet are believed to be correct based on our best knowledge. Therefore, any information is given on condition that users shall make their own assessment of suitability of the product for a specific purpose. We accept no liability for any use or application unless explicitly stated by us. These data are not to be considered as specification.

**All values stated in the properties are typical numbers only.**